@



**FABPRO MANUFACTURING INC.** 3000 E. Preston Street Baltimore, MD 21213 Tel 410-325-5040 HAZARD RATING 4=EXTREME 3=HIGH 2=MODERATE 1=SLIGHT He 0=INSIGNIFICANT B=GOGGLES & GLOVES

Fire 0 Reactivity Health B Special

Internet: <u>www.fabpro.com</u>

CHEMICAL NAME SYNONYMS

TRADE NAME SYNONYMS

 $\langle \mathbf{f} \rangle$ 

CHEMICAL FAMILY SOLUTIONS 1-410-325-5040

**2 HAZARDS IDENTIFICATION** 

**C-50 TRAFFIC SPOTTER** 

## HEALTH HAZARD DATA: GHS Classification:

Signal word: Warning: Irritant, harmful if swallowed.

ROUTES OF EXPOSURE		
INHALATION	IRRITANT	
SKIN ABSORPTION	MAY BE TOXIC BY SKIN ABSORPTION	
SKIN CONTACT	IRRITATING	
EYE CONTACT	IRRITATING	
INGESTION	MAY CAUSE NAUSEA	

	<b>3</b> COMPOSITION/INFORMATION ON INGREDIENTS				
MATERIAL OR COMPONENT	%	CAS NUMBER			
2-BUTOXYETHANOL	1-3	111-76-2			
SODIUM SILICATE	2-6	6834-90-0			
EDTA TETRA SODIUM	3-7	64-02-8			
OCTENYLSUCCINIC ACID	1-8	28805-58-5			

4 FIRST AID MEASURES				
EFFECTS OF OVEREXPOSURE				
ACUTE OVEREXPOSURE	UNKNOWN			
CHRONIC OVEREXPOSURE	UNKNOWN			
EMERGENCY FIRST AID PROCEDURES				
EYES	FLUSH WITH WATER 15 MINUTES AND CALL A PHYSICAN			
SKIN	WASH WITH WATER			
	WASH CONTAMINATED CLOTHING BEFORE REUSE			
INHALATION	MOVE TO FRESH AIR AND CALL A PHYSICIAN			
INGESTION	DO NOT INDUCE VOMITING. CALL A PHYSICIAN			
NOTES TO PHYSICIAN	NOTE HIGH ALKALINITY AND SOLVENT CONTENT pH 13			

5 FIRE FIGHTING MEASURES				
FLASH POINT (TEST METHOD)	N/A	AUTOIGNITION TEMPERATURE N/A		
FLAMMABLE LIMITS IN AIR % BY VOL	LOWER	N/A	UPPER	N/A
EXTINGUISHING MEDIA	N/A		·	
SPECIAL FIRE				
FIGHTING PROCEDURES	N/A			
UNUSUAL FIRE AND				
EXPLOSION HAZARD	N/A			

	<u>6 ACCIDE</u>	NTAL RELEAS	<u>se meas</u> t	JRE	
STEPS TO BE TAKEN IF MATERIAL IS REL					WITH WATER AND FLUSHED
			FEDERAL	, STATE AND	LOCAL REGULATIONS
NEUTRALIZING CHEMICALS:	VINEC				
WASTE DISPOSAL METHOD:	IN AC	CORDANCE W	TTH FEDI	CRAL, STATE	AND LOCAL REGULATIONS
		NDLING & STO		WAGIETIO	
AVOID CONTACT WITH SKIN AND EYES.	AVOID	BREATHING V	APORS.	WASH THO	ROUGHLY AFTER HANDLING.
STORAGE PROCEDURES: STORE IN A COOL I	DRY WEL	LL VENTILATE	ED AREA A	AVOID FREE	ZING OR EXCESSIVE HEAT
8 EXPOS	URE CON	TROLS/PERSO	ONAL PRC	TECTION	
SPECIFIC PERSONAL PROTECTIVE EQUI	PMENT	NONE			
RESPIRATORY (SPECIFY IN DETAIL		IF IN ENCLO	SED ARE	A, USE NIOSF	I MASK
EYE GOGGLES		GLOVES	RUBBE	R	
OTHER CLOTHING AND EQUIPMENT		NONE			
		PHYSICAL DA			
BOILING POINT 760 MM HG	100°C	MELTING PO			O°C pH: 13
SPECIFIC GRAVITY	1.01	VAPOR PRES			SIMILAR TO WATER
VAPOR DENSISTY(AIR-1)	N/A	SOLUBILITY			COMPLETE
% VOLATILES BY WT	84			`````	TATE=1) APPROX=WATER
APPEARANCE AND ODOR		CLEAR BLUI	E LIQUID,	LIGHT SOLV	/ENT ODOR
	10 STAI	BILITY & REA	CTIVITY		
<b>CONDITIONS CONTRIBUTING TO INSTAB</b>	SILITY				NONE
INCOMPATIBILITY					ACIDS
HAZADOUS DECOMPOSITION PRODUCTS				FUMES IF HI	EATED TO DECOMPOSITION
<b>CONDITIONS CONTRIBUTING TO HAZAR</b>	DOUS PO	LYMERIZATI	ON		NONE
11	I TOXICO	DLOGICAL INF	ORMATI	ON	
NONE KNOWN					
	12 ECOL	OGICAL INFO	RMATION	N	
NONE KNOWN					
	13 DISPC	DSAL CONSIDE	ERATIONS	5	
IN ACCORDANCE TO APPLICABLE FEDER	RAL STAT	<b>FE AND LOCA</b>	L REGULA	ATIONS	
	14 TRAN	<b>SPORT INFOR</b>	RMATION		
<b>REFER TO BILL OF LADING OR CONTAIN</b>					
15 REGULATORY INFORMATION					
USA (TSCA), CANADA (DSL)	_ *				
	16 O	THER INFORM	ATION		
		HANDLING		KEEP OUT	OF REACH OF CHILDREN
DISCLAIMER OF LIABILITY					
One should always use chemicals with an away					
system. We urge users to minimize employee e commensurate with good industrial hygiene pr		) all chemicals, i	ncluding th	us product, an	a to keep the level of exposure
The manufacturer and seller warrant that this		onforms to its s	tandard en	ecifications wh	en used according to directions
As the conditions or methods of use are beyon					
for use of this product. Information contained					
without any warranty, expressed or implied, r	egarding a	ccuracy of the i			
material and the results to be obtained from the			I F		
ND-NOT DETERMINED		OT APPLICAE -2014 - C-50 TR		оттер	NE-NOT ESTABLISHED
	x i iy UO-i U-	-4014 - 1,-30 1 K	AFFIC 5F		