SAFETY DATA SHEET								
1 PRODUCT IDENTIFICATION								
FABPRO MANUFACTURING INC. 3000 E. Preston Street Baltimore, MD 21213 Tel 410-325-5040 Internet: www.fabpro.com			HAZARD RATING 4=EXTREME 3=HIGH 2=MODERATE 1=SLIGHT 0=INSIGNIFICANT	ity				
CHEMICAL NAME SYNONYM		RE	CHEMICAL FAMILY: MIX. OXIDIZING AGENTS					
TRADE NAME SYNONYM RXIDE FOR								
2 HAZARDS IDENTIFICATION								
HEALTH HAZARD DATA: GHS Classification: Signal word: Warning: Irritant, harmful if swallowed.								
ROUTE OF EXPOSURE								
INHALATION	YES-IRRITATING TO NOSE AND THROAT							
SKIN ABSORPTION	NO							
INGESTION	YES-CAN CAUSE DISCOMFORT IF TAKEN INTERNALLY							
SKIN CONTACT	NO							
EYE CONTACT	YES-DIRECT CONTACT MAY CAUSE IRRITATION							
3 COMPOSITION/INFORMATION ON INGREDIENTS								
MATERIAL OR COMPONENT	% CAS NUMBER							
POTASSIUM HYDROGEN PEROXYMONOSULFATE	70-100	0-100 70693-62-8						
POTASSIUM CARBONATE	01-10	584-08-7						
4 FIRST A	ID MEAS	URES						
EFFECTS OF OVEREXPOSURE								
ACUTE OVEREXPOSURE	UNKNOWN							
EFFECTS OF OVEREXPOSURE	UNKNOWN							
EMERGENCY FIRST AID PROCEDURES								
EYES: FLUSH WITH WATER FOR 15 MINUTES	SKIN: WASH WITH WATER THOROUGHLY							
IF IRRITATION PERSISTS SEE A PHYSICIAN	IF IRRITATION PERSISTS SEE A PHYSICIAN							
INHALATION: MOVE TO FRESH AIR	INGESTION: DRINK MILK OR WATER							
IF IRRITATION PERSISTS SEE A PHYSICIAN	AND SEE A PHYSICIAN							
NOTES TO PHYSICIAN:								
5 FIRE FIGHTING MEASURES								
FLASH POINT (TOC)		AUT	DIGNITION TEMPERATURE N	/ A				
FLAMMABLE LIMITS IN AIR % BY VOL. LOWER	N/A	UPPE	CR N	I/A				
EXTINGUISING MEDIA	FOAM,	C O2, I	DRY CHEMICAL, WATER FOG					
SPECIAL FIRE FIGHTING PROCEDURES	USUAL FIRE FIGHTING PROCEDURES CAN BE USED							
UNUSUAL FIRE AND EXPLOSION HAZARD	WHEN MOIST CAN LIBERATE HEAT AND OXYGEN							

6-ACCIDENTAL RELEASE MEASURES							
STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: FLUSH WITH WATER, (NON-HAZARDOUS WASTE)							
NEUTRALIZING CHEMICALS							
WASTE DISPOSAL METHOD: WASTE MAY BE DISCHARGED INTO SANITARY SEWER AS NON-HAZARDOUS WASTE							
IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS							
7 HANDLING & STORAGE							
KEEP AWAY FROM HEAT, KEEP AWAY FROM MOISTURE AND ORGANICS AND COMBUSTIBLE AREAS.							
8 EXPOSURE CONTROL/PERSONAL PROTECTION							
SPECIFIC PERSONAL PROTECTIVE EQUIPMENT RESPIRATORY (SPECIFY IN DETAIL)							
DUST MUSK, AVOID BREATHING DUST	NORMAL ROOM VENTILATION SHOULD BE SUFFICIENT						
EYE: MONOGOGGLES SUGGESTED		GLOVES: CONTACT IMPERMEABLE GLOVES SUGGESTED					
OTHER CLOTHING AND EQUIPMENT		AVOID BREATHING VAPOR					
		SICAL DATA					
BOILING POINT:	N/A	MELTING POINT:	ND	рН: 6.0-8.0			
SPECIFIC GRAVITY	1.1	VAPOR PRESSURE	N/A				
VAPOR DENSITY(AIR=1)	N/A	SOLUBILITY IN H ₂ O BY WT.	22-25%				
%VOLATILES BY WT.		EVAPORATION RATE	N/A				
		(BUTYL ACETATE=1)					
APPEARANCE AND ODOR		WHITE FREE FLOWING POW	DER				
10: STABILITY & REACTIVITY							
CONDITIONS CONTRIBUTING TO INSTABILITY, MOISTURE, HEAT, ORGANIC MATERIALS	YES	INCOMPATIBILITY REDUCING AGENTS STRONG ACIDS, ORGANICS					
HAZARDOUS DECOMPOSITION PRODUCTS	YES	CONDITIONS CONTRIBUTING TO NONE					
LIBERATES OXYGEN		HAZARDOUS POLYMERIZATION					
11: TOXICOLOGICAL INFORMATION							
NONE KNOWN							
12: ECOLOGICAL INFORMATION							
NONE KNOWN							
13: DISPOSAL CONSIDERATIONS							
IN ACCORDANCE TO APPLICABLE FEDERAL STATE AND LOCAL REGULATIONS							
14:TRANSPORT INFORMATION							
REFER TO BILL OF LADING OR CONTAINER LABEL							
15:REGULATORY INFORMATION							
USA (TSCA), CANADA (DSL)							
16:OTHER INFORMATION							
PRECAUTIONARY STATEMENTS WASH AFTER HANDLING AND KEEP OUT OF REACH OF CHILDREN							
DISCLAIMER OF LIABILITY							
One should always use chemicals with an awareness of the potential hazard (known and unknown) of their effect on the human							
system. We urge users to minimize employee exposure to all chemicals, including this product, and to keep the level of exposure							
commensurate with good industrial hygiene practices. The manufacturer and seller warrant that this product conforms to its standard specifications when used according to directions.							
As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability							
for use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made							
without any warranty, expressed or implied, regarding							
material and the results to be obtained from the use the							
		PLICABLE	NE-NO	Г ESTABLISHED			
DATE 06-10-2014 - RXIDE FOR BROWNING							