

SAFETY DATA SHEET

1 PRODUCT IDENTIFICATION

FABPRO®

FABPRO MANUFACTURING INC.

3000 E. Preston Street Baltimore, MD 21213

Tel 410-325-5040

Internet: www.fabpro.com

HAZARD RATING


4=EXTREME

3=HIGH

2=MODERATE

1=SLIGHT

0=INSIGNIFICANT



CHEMICAL NAME SYNONYM

MIXTURE

CHEMICAL FAMILY: ACRYLIC EMULSION

TRADE NAME SYNONYM

SOOT SEALER

2 HAZARDS IDENTIFICATION

HEALTH HAZARD DATA: GHS Classification:



Signal word: Warning: Irritant, harmful if swallowed.

ROUTE OF EXPOSURE

INHALATION

YES-IRRITATING TO NOSE AND THROAT

SKIN ABSORPTION

NO

INGESTION

YES-CAN CAUSE DISCOMFORT IF TAKEN INTERNALLY

SKIN CONTACT

NO

EYE CONTACT

YES-DIRECT CONTACT MAY CAUSE SEVERE IRRITATION

3 COMPOSITION/INFORMATION ON INGREDIENTS

| MATERIAL OR COMPONENT | % | CAS NUMBER |
|--------------------------|------|------------|
| MODIFIED ACRYLIC POLYMER | 2-14 | NO CAS |
| ETHANOL | 3-9 | 64-17-5 |
| AMMONIA | 2-9 | 7664-41-7 |

4 FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE

ACUTE OVEREXPOSURE

UNKNOWN

EFFECTS OF OVEREXPOSURE

UNKNOWN

EMERGENCY FIRST AID PROCEDURES

**EYES: FLUSH WITH WATER FOR 15 MINUTES
IF IRRITATION PERSISTS SEE A PHYSICIAN**

**SKIN: WASH WITH WATER THOROUGHLY
IF IRRITATION PERSISTS SEE A PHYSICIAN**

**INHALATION: REMOVE TO FRESH AIR
IF IRRITATION PERSISTS SEE A PHYSICIAN**

**INGESTION: DRINK MILK OR WATER
AND SEE A PHYSICIAN**

NOTES TO PHYSICIAN:

5 FIRE FIGHTING MEASURES

| | | | |
|--|---|---------------------------------|------------|
| FLASH POINT (TOC) | +200°F | AUTOIGNITION TEMPERATURE | N/A |
| FLAMMABLE LIMITS IN AIR % BY VOL. LOWER | N/A | UPPER | N/A |
| EXTINGUISHING MEDIA | FOAM, CO2, DRY CHEMICAL, WATER FOG | | |
| SPECIAL FIRE FIGHTING PROCEDURES | USUAL FIRE FIGHTING PROCEDURES CAN BE USED | | |
| UNUSUAL FIRE AND EXPLOSION HAZARD | NONE KNOWN | | |

| | | | | |
|--|---|---|-----------------------------------|-------------|
| 6-ACCIDENTAL RELEASE MEASURES | | | | |
| STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: FLUSH WITH WATER, (NON-HAZARDOUS WASTE) | | | | |
| NEUTRALIZING CHEMICALS | | | | |
| WASTE DISPOSAL METHOD: WASTE MAY BE DISCHARGED INTO SANITARY SEWER AS NON-HAZARDOUS WASTE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS | | | | |
| 7 HANDLING & STORAGE | | | | |
| KEEP AWAY FROM HEAT; KEEP AWAY FROM EYES AND AVOID PROLONG CONTACT WITH SKIN | | | | |
| | | | | |
| 8 EXPOSURE CONTROL/PERSONAL PROTECTION | | | | |
| SPECIFIC PERSONAL PROTECTIVE EQUIPMENT RESPIRATORY PROTECTION REQUIRED WHEN SPRAYING PRODUCT | | RESPIRATORY (SPECIFY IN DETAIL) NORMAL ROOM VENTILATION SHOULD BE SUFFICIENT | | |
| EYE: MONOGOGGLES SUGGESTED | | GLOVES: CONTACT IMPERMEABLE GLOVES SUGGESTED | | |
| OTHER CLOTHING AND EQUIPMENT | | NONE | | |
| 9: PHYSICAL DATA | | | | |
| BOILING POINT: | 100°C | MELTING POINT: | BELOW 40°F | pH: 6.0-8.0 |
| SPECIFIC GRAVITY | 1.02 | VAPOR PRESSURE | ND | |
| VAPOR DENSITY(AIR=1) | >1 | SOLUBILITY IN H ₂ O BY WT. | SOLUBLE | |
| %VOLATILES BY WT. | | EVAPORATION RATE (BUTYL ACETATE=1) | >1 | |
| APPEARANCE AND ODOR | | HAZY LIQUID, ACRYLIC ODOR | | |
| | | | | |
| 10: STABILITY & REACTIVITY | | | | |
| CONDITIONS CONTRIBUTING TO INSTABILITY | NONE | INCOMPATIBILITY | ACIDS, STRONG OXIDIZING AGENTS | |
| HAZARDOUS DECOMPOSITION PRODUCTS WHEN EXPOSED TO FIRE EMITS NORMAL PRODUCTS OF COMBUSTION | YES | CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION | NONE | |
| 11: TOXICOLOGICAL INFORMATION | | | | |
| NONE KNOWN | | | | |
| | | | | |
| 12: ECOLOGICAL INFORMATION | | | | |
| NONE KNOWN | | | | |
| 13: DISPOSAL CONSIDERATIONS | | | | |
| IN ACCORDANCE TO APPLICABLE FEDERAL STATE AND LOCAL REGULATIONS | | | | |
| 14:TRANSPORT INFORMATION | | | | |
| REFER TO BILL OF LADING OR CONTAINER LABEL | | | | |
| 15:REGULATORY INFORMATION | | | | |
| USA (TSCA), CANADA (DSL) | | | | |
| 16:OTHER INFORMATION | | | | |
| PRECAUTIONARY STATEMENTS | WASH AFTER HANDLING AND KEEP OUT OF REACH OF CHILDREN | | | |
| DISCLAIMER OF LIABILITY | | | | |
| One should always use chemicals with an awareness of the potential hazard (known and unknown) of their effect on the human system. We urge users to minimize employee exposure to all chemicals, including this product, and to keep the level of exposure commensurate with good industrial hygiene practices. The manufacturer and seller warrant that this product conforms to its standard specifications when used according to directions. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information. The hazards connected with the use of the material and the results to be obtained from the use thereof. | | | | |
| ND-NOT DETERMINED | NA-NOT APPLICABLE | | NE-NOT ESTABLISHED | |
| DATE 06-10-2014 - SOOT SEALER | | | | |